



Accu-Drill SD

AUTOMATED HOLE DRILLERS

The Accu-Drill SD Automated Hole Driller is a powerful, safe solution for catheter hole drilling and skiving patterns requiring one to four axes of control. The automatic hole-plug ejector pin system and coordinated hole-plug blow off and vacuum collection system **cleanly remove scrap material**. With full-color LCD touchscreen HMI, pattern memory, and adjustable feed and speed controls, achieve **total control** and **uncompromising precision**. Paired with our powerful SYNEO cutting tools, realize **unmatched hole quality**.



KEY FEATURES

- Industry's fastest and most reliable machines for quality catheter holes and skives
- Full-color LCD touchscreen HMI with pattern memory systems
- Easy cutting tool and catheter guide changes
- Efficient control and collection of hole plugs and skive debris
- Configurable for any type of catheter requirement

UNIVERSAL SPECIFICATIONS

- Spindle speed:** 0 - 4,000rpm
- Drill depth setting resolution:** .001" (.025mm)
- Drill Chuck Run-out:** .0002" (.005mm) TIR
- Drill chuck:** .125" (3.17mm) diameter
- Power:** 110VAC at 50/60Hz
- Air:** 30-120psi

COMMONLY PROCESSED MATERIALS

- Teflon® PTFE
- Polyimide
- Polyurethane
- PET
- Polyethylene
- Nylon 6 and small diameter nylon 12
- Teflon® FAP
- Pebax®
- PVC (vinyl)
- Polycarbonate
- Latex and natural rubber
- Silicone
- PEEK
- TPE
- Acrylic

AVAILABLE MODELS

Accu-Drill SD100

One Axis (Z-axis)

Orientation: Vertical
Operating speed: Average 1.3 seconds per hole
Memory: Single program

Accu-Drill SD200

Two Axes (R- and Z-axis)

Orientation: Vertical
Operating speed: Average 1.3 seconds per hole
Memory: 16 patterns containing up to 8 holes per pattern
Graspers: 3fr -9fr, 10fr – 18fr, 19fr – 28fr

Accu-Drill SD300/C

Three Axes (X-, R-, and Z-axis)

300 Orientation: Horizontal | **300C Orientation:** Custom, Vertical
Operating speed: Average 1.3 seconds per hole
Memory: 16 patterns containing up to 30 holes per pattern
X-axis travel: 6" (15.2cm)
Graspers: 3fr -9fr, 10fr – 18fr, 19fr – 28fr

Accu-Drill SD400/C

Four Axes (X-, Y-, R-, and Z-axis)

400 Orientation: Horizontal | **400C Orientation:** Custom, Vertical
Operating speed: Average 1.2 seconds per hole
Memory: 80 patterns containing up to 80 holes per pattern
X-axis travel: 9.25" (23.5cm)
Y-axis travel: 1.75" (4.4cm)
Graspers: 3fr -9fr, 10fr – 18fr, 19fr – 28fr

Accu-Drill SD

AUTOMATED HOLE DRILLERS

OPTIONS	SD100	SD200	SD300	SD400
Manually adjustable X and/or Y positioning stages	•	•		
Digital microscope and LCD monitor	•	•	•	•
.156" (3.99mm) diameter capacity drill chuck	•	•	•	•
.062" (1.57mm) diameter capacity micro drill chuck	•	•	•	•
220VAC conversion	•	•	•	•
Vacuum hole-plug collection	•	<i>Standard feature</i>	<i>Standard feature</i>	<i>Standard feature</i>
Hole-plug detection systems	•	•	•	•
Machine vision system	•	•	•	•
Longer X-Axis travel				
Catheter drilling and skiving guides	•	•	•	•
Mechanical catheter graspers	•			
Manual catheter positioning (rotational and linear)	•			
Keyed lumen positioning fixtures	•	•	•	•
Custom part nests	•	•	•	•
R-axis motor tooling		•	•	•
Micro-adjustable bridge and pier assembly		•		
Adjustable R-axis motor mount		•		
Rotating drilling head mount	•	•		
Ultra-precision collet spindle with Levin WW collet	•	•	•	•
Lumen locating sensor package			•	•
Pneumatic skiving stabilizer	•	•	•	•
Recipe standard				
Recipe extended			•	•



An MMT Company

SYNEO is proud to be an MMT company – the sole source for automated, process-driven medical manufacturing.

Medical Manufacturing Technologies (MMT) brings together applications expertise, technical solutions, and aftermarket support to revolutionize medical device manufacturing. [Learn more at mmt-inc.com](http://mmt-inc.com).